

Application No. 10/719,515  
Response to OA of 04/04/2006

RECEIVED  
CENTRAL FAX CENTER

JUL 03 2006

**Listing of the Claims**

**This listing of claims will replace all prior versions, and listings, of the claims:**

1. (original) A method for storing data on and retrieving data from a magnetic tape comprising:
  - receiving data when operating in a write mode;
  - passing magnetic tape across an electromagnetic head;
  - varying drive current to the electromagnetic head according to the data when operating in a write mode;
  - sensing current induced in the electromagnetic head when operating in a read mode;
  - sensing vibration imparted to a tape transport mechanism; and
  - adjusting position of the electromagnetic head according to the sensed vibration.
2. (original) The method of claim 1 wherein sensing the vibration comprises generating an electrical signal according to the vibration experienced by a tape transport mechanism.
3. (original) The method of claim 1 wherein adjusting the position comprises:
  - generating a correction signal based on vibration information; and
  - positioning the electromagnetic head according to the correction signal.
4. (original) The method of claim 3 further comprising limiting vibration frequencies imparted to the tape transport mechanism in accordance with a frequency response of positioning the electromagnetic head.
5. (original) The method of claim 3 wherein generating a correction signal comprises:
  - receiving a vibration indicative signal; and
  - modifying the vibration indicative signal through compensation in order to improve the response of positioning the electromagnetic head.

Application No. 10/719,515  
Response to OA of 04/04/2006

6. (original) The method of claim 3 wherein generating a correction signal comprises:
  - receiving a vibration indicative signal; and
  - modifying the vibration indicative signal through prediction in order to improve the response of positioning the electromagnetic head.
7. (original) The method of claim 6 wherein modifying the vibration indicative signal through prediction comprises:
  - analyzing the spectral composition of the vibration indicative signal; and
  - predicting a future vibration value according to the spectral composition.
8. (original) The method of claim 1 further comprising:
  - sensing a position of the magnetic tape relative to the electromagnetic head; and
  - adjusting the position of the electromagnetic head according to the sensed position of the magnetic tape.
9. (original) The method of claim 1 further comprising precluding variations in the drive current to the electromagnetic head when the sensed vibration exceeds a pre-established rate of change.
10. (original) An electromagnetic head assembly comprising:
  - electromagnetic head;
  - vibration sensor capable of sensing vibration imparted to the electromagnetic head assembly; and
  - head positioning unit capable of adjusting the position of the electromagnetic head according to the sensed vibration.
11. (original) The electromagnetic head assembly of claim 10 wherein the vibration sensor is attached to the electromagnetic head assembly and is capable of generating a vibration indicative signal.

Application No. 10/719,515  
Response to OA of 04/04/2006

12. (original) The electromagnetic head assembly of claim 10 wherein the head positioning unit comprises:

correction signal generator capable of generating a correction signal based on vibration information received from the vibration sensor; and

head position actuator capable of positioning the electromagnetic head according to the correction signal.

13. (original) The electromagnetic head assembly of claim 12 further comprising a vibration limiter capable of limiting vibration frequencies of a chassis whereon the electromagnetic head is mounted in accordance with the frequency response of head positioning.

14. (original) The electromagnetic head assembly of claim 12 wherein the correction signal generator comprises:

vibration signal receiver capable of receiving a vibration indicative signal from the vibration sensor; and

vibration signal processor capable of modifying the vibration indicative signal by applying compensation in order to improve the response of head positioning.

15. (original) The electromagnetic head assembly of claim 12 wherein the correction signal generator comprises:

vibration signal receiver capable of receiving a vibration indicative signal from the vibration sensor; and

vibration signal processor capable of modifying the vibration indicative signal by applying prediction in order to improve the response of head positioning.

16. (original) The electromagnetic head assembly of claim 15 wherein the vibration signal processor comprises:

spectrum analysis unit capable of analyzing the spectral composition of the vibration indicative signal; and

Application No. 10/719,515  
Response to OA of 04/04/2006

prediction unit capable of predicting a future vibration value according to the spectral composition.

17. (original) The electromagnetic head assembly of claim 10 further comprising:  
tape position sensor capable of generating a tape position signal according to the position of the magnetic tape wherein the head positioning unit further is capable of adjusting the position of the electromagnetic head according to the tape position signal.

18. (original) The electromagnetic head assembly of claim 10 further comprising a comparison unit capable of generating a signal that precludes variations in the drive current to the electromagnetic head when the sensed vibration exceeds a pre-established rate of change.

19. (original) A magnetic tape drive comprising:  
tape transport mechanism for transporting magnetic tape;  
interface module capable of generating a head drive signal according to received data;  
electromagnetic head capable of generating a magnetic field according to the head drive signal;  
accelerometer that senses vibration imparted to the tape transport mechanism in a control axis; and  
head position control system capable of adjusting the position of the electromagnetic head along the control axis according to the sensed vibration.

20. (original) The magnetic tape drive of claim 19 wherein the accelerometer is attached to the tape transport mechanism and is capable of generating a vibration indicative signal according to vibration along the control axis.

21. (original) The magnetic tape drive of claim 19 wherein the head position control system comprises:

Application No. 10/719,515  
Response to OA of 04/04/2006

correction signal generator capable of generating a correction signal based on the vibration indicative signal received from the accelerometer; and

head position actuator capable of positioning the electromagnetic head according to the correction signal.

22. (original) The magnetic tape drive of claim 21 further comprising an isolation mount capable of limiting vibration frequencies of the tape transport mechanism in accordance with the frequency response of head positioning.

23. (original) The magnetic tape drive of claim 21 wherein the correction signal generator comprises:

vibration signal receiver capable of receiving a vibration indicative signal from the accelerometer; and

vibration signal processor capable of modifying the vibration indicative signal by applying compensation in order to improve the response of the head position actuator.

24. (original) The magnetic tape drive of claim 21 wherein the correction signal generator comprises:

vibration signal receiver capable of receiving a vibration indicative signal from the accelerometer; and

vibration signal processor capable of modifying the vibration indicative signal by applying prediction in order to improve the response of the head position actuator.

25. (original) The magnetic tape drive of claim 24 wherein the vibration signal processor comprises:

analog-to-digital converter that creates a digital representation of the vibration indicative signal;

memory capable of storing instructions; digital signal processor capable of executing instruction sequences; and

digital signal processing instruction sequences stored in the memory comprising: spectrum analysis instruction sequence that, when executed by the digital signal

Application No. 10/719,515  
Response to OA of 04/04/2006

processor, minimally causes the processor to compute a transform of the digital representation, p2 prediction instruction sequence that, when executed by the digital signal processor, minimally causes the digital signal processor to compute a future value of the digital representation according to the transform, and digital-to-analog converter that creates an analog control signal according to the future value of the digital representation.

26. (original) The magnetic tape drive of claim 19 further comprising:

tape position sensor capable of generating a tape position signal according to the position of the magnetic tape wherein the head position control system further is capable of adjusting the position of the electromagnetic head according to the tape position signal.

27. (original) The magnetic tape drive of claim 19 further comprising a comparator that generates a signal that precludes variations in the drive current to the electromagnetic head when the derivative of the sensed vibration exceeds a pre-established value.

28. (original) A tape head positioning system comprising:

means for imparting information onto magnetic tape;  
means for supporting the information imparting means;  
means for sensing vibration applied to the supporting means; and  
means for adjusting position of the information imparting means to compensate for potential errors induced by the vibration.

29. (original) The tape head positioning system of claim 28 wherein the vibration sensing means generates an electrical signal according to the vibration experienced by the supporting means.

30. (original) The tape head position system of claim 28 wherein the position adjusting means comprises:

means for generating a correction signal according to vibration sensed by the vibration sensing means; and means for adjusting the position of the information

Application No. 10/719,515  
Response to OA of 04/04/2006

imparting means according to the correction signal.

31. (original) The tape head position system of claim 30 further comprising means for limiting vibration frequencies imparted to the supporting means in accordance with the frequency response of tape head positioning.

32. (original) The tape head position system of claim 30 wherein the correction signal generating means comprises:

means for receiving a vibration indicative signal; and

means for modifying the vibration indicative signal through compensation in order to improve the response of tape head positioning.

33. (original) The tape head position system of claim 30 wherein the correction signal generating means comprises:

means for receiving a vibration indicative signal; and

means for modifying the vibration indicative signal through prediction in order to improve the response of tape head positioning.

34. (original) The tape head position system of claim 33 wherein the signal modifying means comprises:

means for analyzing the spectral composition of the vibration indicative signal;

and

means for predicting a future vibration value according to the spectral composition.

35. (original) The tape head position system of claim 28 further comprising:

means for sensing the position of the magnetic tape; and

means for adjusting the position of the information imparting means according to the sensed position of the magnetic tape.

36. (original) The tape head position system of claim 28 further comprising means for

Application No. 10/719,515  
Response to OA of 04/04/2006

precluding variations in the drive current to the electromagnetic head when the sensed vibration exceeds a pre-established level or rate of change or any other quantity deemed suitable for the purpose.